

## TECHNICAL SPECIFICATIONS

Description	Unit	Logicool Split		
		1.2	1.5	2.0
Tonnage Class	Tr.	1.2	1.5	2.0
Star Rating	No of BEE Stars	5	5	3
Unit	Model Number	LRAU514KSDB	LRAU518KSDB	LRAU323KSDB
IDU	Model Number	LRAS514KSDB	LRAS518KSDB	LRAS323KSDB
ODU	Model Number	LRAC514KSDB	LRAC518KSDB	LRAC323KSDB
Compressor	Type	ROTARY	ROTARY	ROTARY
Rated Cooling Capacity	BTU/Hr	13819	18460	22520
Rated Cooling Capacity	Watts	4050	5410	6600
Rated Power Supply	Volts/Hz/Phase	230/50/1	230/50/1	230/50/1
Total Power Input	Watts	1190	1590	2230
EER	Rated Cooling Capacity (BTU/Hr) / Power Input (Watts)	11.61	11.61	10.10
COP	Rated Cooling Capacity (Watts) / Power Input (Watts)	3.40	3.40	2.96
Current Drawn	Amps	5.25	7.12	10.00
Fan Speed	Steps	3	3	3
Air Flow (IDU) (Super High)	CFM	424	636	636
Sound Level* (IDU)	dB	40	40	40
Dimension (IDU) (W X H X D)	mm	830 X 290 X 220	1050 X 290 X 220	1050 X 290 X 220
Dimension (ODU) (W X H X D)	mm	750 X 548 X 288	792 X 600 X 299	792 X 600 X 299
Net Weight (IDU)	Kg	10	12.9	12.9
Net Weight (ODU)	Kg	35.4	41	44.5
Remocon	Type	Wireless LCD	Wireless LCD	Wireless LCD

Features may vary from model to model.

\*At Super silent fan speed & at a distance of 1 m .

Hitachi Air Conditioners are designed to work in ambient temperatures up to 52°C.

Due to continuous research & development, specifications & features may change without prior notice.